



EDL-420/WS

Order No.: 0161880

PRODUCTINFOS

Weatherproof PA ball speaker

- 100 V transmission technology or 8 Ω operation
- White ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with 480 cm connection cable and canopy

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

EDL-420/WS

Active/passive

passive

EDL-420/WS

Transmission technology	100 V or low-impedance
Total power rating	20 W
Power rating (RMS)	20/10/5 W
Impedance	8 Ω
Frequency range	120-20,000 Hz
Full range speaker	160 mm (6")
Number of speakers	1
Speaker size	15 cm (6")
SPL	94 dB/W/m
Radiation angle/beam angle	100°
Radiation angle, horizontal	100°
Radiation angle, vertical	100°
Housing material	ABS, UL 94 V-0
Colour	white
Mounting device	cable with canopy
Admiss. ambient temp.	-30 °C to +40 °C
Dimensions	Ø 265 mm
Width	Ø 265 mm
Height	Ø 265 mm
Depth	265 mm
Weight	2.3 kg
Inputs	cable connection
Packaging dimensions (W x H x L)	0.305 x 0.28 x 0.38 m
Gross weight	2.84 kg
Net weight	2.34 kg

EDL-420/WS

EAN code	4007754189148
Net weight	2.34 kg