



SL-150SW/EN

Order No.: 1001155

PRODUCTINFOS

Weatherproof PA speaker system with 20 cm (8") coaxial horn speaker,

developed for outdoor applications, with an excellent sound quality. The SL-150SW/EN is ideally suited for applications at versatile locations, e.g. airports, megastores and stadiums.

Weatherproof PA speaker system, 150 W,

with EN 54-24 certification.

- 100 V transmission technology or 8 Ω operation
- 2-way bass-reflex system
- 20 cm (8") coaxial speaker with tweeter and crossover network
- Excellent sound
- IP66 tested
- ABS cabinet with metal grille
- Recessed connection terminal with cover plate and high-strength cable gland
- Supplied with safety rope
- Stainless steel wall bracket

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS**SL-150SW/EN**

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	150 W
Power rating (RMS)	150/75/38 W
Impedance	8 Ω
Frequency range	90-19,000 Hz
System	2-way coaxial
Bass speaker	20 cm (8")
Tweeter	tweeter
Number of speakers	2
Speaker size	20 cm (8")
SPL	98 dB/W/m
Max. rated SPL	120 dB
Radiation angle/beam angle	H: 80°/V: 80°
Radiation angle, horizontal	80°
Radiation angle, vertical	80°
Housing material	ABS
Colour	black
Mounting device	mounting bracket
Protection class	IP66
Admiss. ambient temp.	-25 °C to +70 °C
Dimensions	315 x 305 x 350 mm
Width	315 mm
Height	305 mm
Depth	350 mm
Weight	11.85 kg
Inputs	screw terminal
Packaging dimensions (W x H x L)	0.39 x 0.47 x 0.39 m

SL-150SW/EN

Gross weight	13.9 kg
Net weight	11.85 kg

SL-150SW/EN

EAN code	4007754425840
Net weight	11.85 kg