



WP-1/WH



Order No.: 1001216

PRODUCTINFOS

Wall module,

for controlling 4-zone multifunctional amplifiers PA-4125DX and PA-4125DX/DT.

- Connection of up to 8 x wall module WP-1/WH or WP-1/BK to each amplifier PA-4125DX and PA-4125DX/DT
- Each wall module can be assigned to any sound zone of PA-4125DX and PA-4125DX/DT via WebControl app
- Source can easily be changed or volume level be kept via preset minimum and maximum volume levels
- PoE for easy network pairing, real-time synchronisation of the devices with the system and power supply of the controller
- PIN code protection for easy and extended access, including switching off the system when leaving the location
- Intuitive menu for simple installation, system setup and an easy user operation
- Adjustable screen and backlight for controlling brightness and colour
- High-performance polymer of Danish design with smooth matt surface and covered screws
- Mounting in standard flush-mounted socket
- EU standard colour white RAL9003

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

WP-1/WH

Description	wall module
Type	remote control of a zone
Colour	white, RAL9003
Suitable for	PA-4125DX
Power supply	PoE, 3.84 W max.
Admiss. ambient temp.	0-40 °C
Dimensions	87 x 87 x 43 mm
Mounting dimensions	mounting depth: 23 mm
Weight	124 g
Connections	1 x RJ45
Other features	cable length: 100 m max.
Packing unit	1
Packaging dimensions (W x H x L)	0.12 x 0.07 x 0.15 m
Gross weight	0.26 kg
Net weight	0.124 kg

WP-1/WH

EAN code	4007754427035
Net weight	0.124 kg