



MKA-50SET/SW

Order No.: 0132350

PRODUCTINFOS

Active 2-way stereo speaker systems, 2 x 20 W

- Set consists of an active and a passive speaker system. Connection of the passive system to the active system via spring-loaded speaker terminals
- Active speaker system with integrated 2-channel amplifier and power supply
- Speakers with magnetic shielding
- Auto-standby function
- Volume control and 2-way tone control

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Safety and warning notices

The appliance is supplied with life-threatening mains voltage. Therefore, never tamper with it yourself and do not insert anything into the ventilation openings. There is a risk of electric shock.

Do not operate the appliance and disconnect the mains plug from the socket immediately if there is visible damage to the appliance or the mains cable, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialist workshop for repair.

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).

Never set the speaker volume very high. High volumes can damage your hearing in the long term!

Never pull the mains plug out of the socket by the cable, always grasp the plug.

If the appliance is to be taken out of service for good, hand it over to a local recycling centre for environmentally friendly disposal.

TECHNICAL SPECIFICATIONS

MKA-50SET/SW

Active/passive	active/passive
Transmission technology	cable
Total output power	2 x 40 W
Power rating (RMS)	2 x 20 W
Frequency range	60-20,000 Hz
Input signal	420 mV/24 kΩ
System	2-way
Bass speaker	13 cm (5") bass-midrange speaker
Tweeter	2.5 cm (1") tweeter
Number of speakers	2
Speaker size	13 cm (5")
SPL	89 dB/W/m
Max. rated SPL	102 dB

MKA-50SET/SW

Radiation angle/beam angle	H: 120°/V: 100°
Radiation angle, horizontal	120°
Radiation angle, vertical	100°
Housing material	plastic
Colour	black
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/110 VA
Dimensions	180 x 250 x 160 mm
Width	180 mm
Height	250 mm
Depth	160 mm
Weight	5.9 kg (pair)
Inputs	1 x RCA L/R (active speak. system only)
	1 x 3.5 mm jack
	screw terminals (both speaker systems)
Other features	pair
Packaging dimensions (W x H x L)	0.21 x 0.27 x 0.435 m
Gross weight	6.36 kg
Net weight	5.87 kg

MKA-50SET/SW

EAN code	4007754241907
Net weight	5.87 kg