




WDE-130-N

Order No.: 1001436

PRODUCTINFOS

PA ceiling speaker, 4 Ω

- Very good transmission range
- Speaker (13 cm) with high sound pressure and very good transmission range
- Moisture-proof speaker cone
- Quick-mounting device
- Metal housing with metal protective grille
- Connection via pressure clamps
- Ball-proof in accordance with DIN 18 032, part 3

Manufacturer information:

PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

TECHNICAL SPECIFICATIONS

WDE-130-N

Impedance (Z)	4 Ω
Transmission technology	cable
Frequency range	60-20,000 Hz
Power rating (RMS)	15 W
SPL	94 dB/W/m
Max. rated SPL	105 dB
Radiation angle, horizontal	180°
Radiation angle, vertical	180°
Mounting cutout	Ø 140-150 mm
Dimensions	Ø 168 mm x 48 mm
Outside diameter	Ø 168 mm
Width	Ø 168 mm
Height	Ø 168 mm
Depth	48 mm
Colour	white, RAL 9010
Protective class	IP54
Weight	0.6 kg
Packing unit	1
Packaging dimensions (W x H x L)	0.187 x 0.187 x 0.075 m
Gross weight	0.8 kg
Net weight	0.7 kg

WDE-130-N

EAN code	4007754429701
Net weight	0.7 kg