



WALL-05SET/WS

Order No.: 0130132

PRODUCTINFOS

Active 2-way stereo speaker system, 2 x 30 W

- Set consists of one active and one passive speaker system. Connection of the passive system to the active system via screw terminal strip
- Active speaker system with integrated 2-channel amplifier
- Stereo RCA input or balanced input L/R via screw terminal strip
- Volume control and 2-way tone control
- Auto standby
- 13 cm (5") bass speaker system and dome tweeter
- Stylish white plastic cabinet
- Mounting bracket for pivoting and tilting

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices

The appliance is supplied with life-threatening mains voltage. Therefore, never tamper with it yourself and do not insert anything into the ventilation openings. There is a risk of electric shock.

Do not operate the appliance and disconnect the mains plug from the socket immediately if there is visible damage to the appliance or the mains cable, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialist workshop for repair.

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).

Never set the speaker volume very high. High volumes can damage your hearing in the long term!

Never pull the mains plug out of the socket by the cable, always grasp the plug.

If the appliance is to be taken out of service for good, hand it over to a local recycling centre for environmentally friendly disposal.

TECHNICAL SPECIFICATIONS

WALL-05SET/WS

Active/passive	active/passive
Transmission technology	cable
Total output power	2 x 50 W
Power rating (RMS)	2 x 30 W
Frequency range	80-20,000 Hz
Input signal	500 mV/20 kΩ (unbal.) 660 mV/40 kΩ (bal.)
System	2-way
Bass speaker	13 cm (5") bass speaker
Tweeter	dome tweeter
Number of speakers	2
Speaker size	13 cm (5")
SPL	89 dB/W/m
Max. rated SPL	104 dB
Radiation angle/beam angle	H: 110°/V: 90°
Radiation angle, horizontal	110°
Radiation angle, vertical	90°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/100 VA
Dimensions	163 x 252 x 203 mm (with bracket)

WALL-05SET/WS

Width	163 mm
Height	252 mm
Depth	203 mm
Weight	5.5 kg (pair)
Inputs	1 x RCA L/R (unbal.)
	1 x terminal L/R (bal.)
	spring-load. speaker term. (passive speaker system)
	spring-load. speaker term.
Other features	pair
Packaging dimensions (W x H x L)	0.2 x 0.28 x 0.425 m
Gross weight	6.9 kg
Net weight	5.63 kg

WALL-05SET/WS

EAN code	4007754271430
Net weight	5.63 kg