



SM-2

Order No.: 0291870

PRODUCTINFOS

Sound level meter,

(class 2), one-hand operation.

- Electret microphone cartridge
- Functions max hold and data hold
- A-weighting and C-weighting, slow and fast
- Additional output for DC/~ V via 3.5 mm jack
- Supplied with practical nylon bag

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

TECHNICAL SPECIFICATIONS

SM-2

Display	3½ digits, LCD, 17 mm
Frequency range	31.5-8,000 Hz
Measuring range, low	35-100 dB
Measuring range, high	65-130 dB
Resolution	0.1 dB
Accuracy	±1.5 dB (94 dB/1 kHz)
Output V~	low: 38 mV/dB, 100 Ω high: 8.3 mV/dB, 100 Ω
Output V DC	10 mV/dB, 100 Ω
Admiss. ambient temp.	0-40 °C
Power supply	9 V battery (not supplied)
Dimensions	63 x 253 x 30 mm
Weight	250 g

SM-2

EAN code	4007754174045
Net weight	0.525 kg