



ESP-62AB/WS



Order No.: 0163660

PRODUCTINFOS

PA A/B wall speaker,

with EN 54-24 certification for voice alarm systems with A/B speaker distribution according to EN 60849.

- 100 V transmission technology
- Full range speaker (13 cm) with dual voice coil
- 2 separate transformers with power taps with 6/3/1.5 W each
- Connection via 2 ceramic screw terminals inside the cabinet
- Symmetrical design allows for horizontal and vertical mounting
- Design plastic cabinet (open rear panel) with protective metal front grille
- Supplied with screws and wall plugs

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

ESP-62AB/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	2 x 6 W
Power rating (RMS)	2 x 6/3/1.5 W
Frequency range	80-19,000 Hz
Full range speaker	13 cm, dual voice coil
Number of speakers	1
Speaker size	13 cm (5")
SPL	93 dB (1 W/1 m)
	76 dB (EN, 1 W/4 m)
Max. rated SPL	101 dB (1 m)
	86 dB (EN, 4 m)
Radiation angle/beam angle	H180°/V180° (500 Hz)
	H180°/V180° (1 kHz)
	H180°/V115° (2 kHz)
	H51°/V68° (4 kHz)
	180° (500 Hz)
Radiation angle, horizontal	180° (1 kHz)
	180° (2 kHz)
	51° (4 kHz)
Radiation angle, vertical	180° (500 Hz)
	180° (1 kHz)
	115° (2 kHz)
	68° (4 kHz)
Housing material	ABS
Colour	white, RAL 9010
Mounting device	screws
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	240 x 330 x 83 mm
Width	240 mm
Height	330 mm
Depth	83 mm
Weight	1.5 kg
Inputs	screw terminals
Packaging dimensions (W x H x L)	0.245 x 0.1 x 0.345 m
Gross weight	1.806 kg
Net weight	1.545 kg

ESP-62AB/WS

EAN code 4007754263855

Net weight 1.545 kg