



ECM-306B/SW

Order No.: 0235790

PRODUCTINFOS

Boundary microphone

- On/off switch with power LED
- Low cut and 10 dB attenuation, switchable
- Integrated electronics for direct connection to a phantom power supply DC 17-48 V
- Electronically balanced AF output
- 6 m connection cable with 3-pole mini XLR/XLR
- Supplied in a foam-padded plastic case

Especially suitable for the use as a desktop microphone!

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

ECM-306B/SW

Description	boundary microphone
Transmission method	cable
Polar pattern	semi-supercardioid
System	electret
Audio frequency range	30-20,000 Hz
Nominal impedance	250 Ω
Sensitivity	22 mV/Pa
Max. sound pressure	130 dB
Power supply	DC 17-48 V, phantom power
Admiss. ambient temp.	0-40 °C
Dimensions	90 x 25 x 90 mm
Weight	200 g
Cable	6 m
Connection	3-pole mini XLR/XLR
Packaging dimensions (W x H x L)	0.16 x 0.085 x 0.28 m
Gross weight	0.453 kg
Net weight	0.289 kg

ECM-306B/SW

EAN code	4007754212723
Net weight	0.289 kg