



SOUND-100SUB

Order No.: 0250730

PRODUCTINFOS

With the 2-way Active Systems and the Subwoofers of the SOUND Series,

efficient speakers with a powerful sound are available in different sizes and with different features. They are all integrated into high-quality bass-reflex MDF cabinets and feature speakers with magnetic shielding. The speaker systems are ideally suited as active hi-fi speaker systems, high-end PC speakers and for small PA applications requiring a powerful sound, e.g. media presentations.

Active subwoofer system, 120 W

- Active subwoofer for adding to the active SOUND speaker systems, but also to any other compact speaker for hi-fi or home cinema applications and home recordings
- Amplifier features variable input sensitivity, a phase switch, an automatic switch-on system which can additionally be activated as well as an adjustable crossover frequency (50-150 Hz)
- High-quality bass-reflex MDF cabinet (black wood veneer look)
- 25 cm (10") bass speaker
- Volume control for the subwoofer
- Inputs via 1 x RCA L/R, RCA LFE or screw terminals for high-level L/R
- Additional outputs for mid-high range speakers, thus well-suited for connection to already existing speaker cables

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices

The appliance is supplied with life-threatening mains voltage. Therefore, never tamper with it yourself and do not insert anything into the ventilation openings. There is a risk of electric shock.

Do not operate the appliance and disconnect the mains plug from the socket immediately if there is visible damage to the appliance or the mains cable, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialist workshop for repair.

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).

Never set the speaker volume very high. High volumes can damage your hearing in the long term!

Never pull the mains plug out of the socket by the cable, always grasp the plug.

If the appliance is to be taken out of service for good, hand it over to a local recycling centre for environmentally friendly disposal.

TECHNICAL SPECIFICATIONS

SOUND-100SUB

Active/passive	active
Transmission technology	cable
Total output power	200 W
Power rating (RMS)	120 W
Frequency range	35-100 Hz
Input signal	150 mV/24 kΩ (RCA L/R)
	55 mV/16 kΩ (RCA mono)
	2.3 V/440 Ω (high IN)
Bass speaker	25 cm (10") bass speaker
Number of speakers	1
Speaker size	25 cm (10")
SPL	88 dB/W/m
Max. rated SPL	108 dB
Radiation angle/beam angle	omnidirectional
Housing material	wood
Colour	black

SOUND-100SUB

Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/240 VA
Dimensions	330 x 360 x 360 mm
Width	330 mm
Height	360 mm
Depth	360 mm
Weight	13 kg
Inputs	1 x RCA (L/R), unbal., IN
	1 x RCA (mono), unbal., IN
	1 x screw terminal (stereo), high-level IN
Outputs	1 x screw terminals (stereo), high-level out
Packaging dimensions (W x H x L)	0.46 x 0.46 x 0.46 m
Gross weight	15.68 kg
Net weight	13.05 kg

SOUND-100SUB

EAN code	4007754212303
Net weight	13.05 kg