



Sample photo

**Order symbol:** PC 121211  
**Product nbr:** 7032690  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074058409  
**EI. number:**  
**Finland:** 3435360  
**Electric No.** 8212002788  
**Denmark:**  
**Electric No. Sweden:** 2536122

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

| Dimensions:                  | Length               | Width | Height | Rating:                                  |
|------------------------------|----------------------|-------|--------|------------------------------------------|
| mm:                          | 122                  | 120   | 105    | Ingress Protection (EN 60529): IP66/IP67 |
| inch:                        | 4.8                  | 4.7   | 4.1    | Impact Resistance (EN 62262): IK07/IK08  |
| Materials:                   |                      |       |        | Electrical insulation: Totally insulated |
| Material:                    | Polycarbonate        |       |        | Halogen free (DIN/VDE 0472, Part 815): 1 |
| Base colour:                 | RAL 7035 -light grey |       |        | UV resistance: UL 508                    |
| Cover screws material:       | Stainless steel      |       |        | Flammability Rating: UL 746C 5"          |
| Cover colour:                | RAL 7035 -light grey |       |        | Glow Wire Test (IEC 695-2-1) °C: 960     |
| Gasket material:             | Polyurethane         |       |        | NEMA Class: NEMA 1, 4, 4X, 12, 13        |
| Temperatures:                |                      |       |        | Certificates:                            |
| Temperature °C (short term): | -40 ... 120 °C       |       |        | SGS Fimko                                |
| Temperature °C (continuous): | -40 ... 80 °C        |       |        | Gost R                                   |
| Temperature °F (short term): | -40 ... 250 °F       |       |        |                                          |
| Temperature °F (continuous): | -40 ... 175 °F       |       |        |                                          |

EURONORD PC/ABS 122x120x65-105

