



EDL-412/WS

Order No.: 0161860

PRODUCTINFOS

Weatherproof PA ball speaker

- 100 V transmission technology or 8 Ω operation
- White ABS housing (self-extinguishing, complies with standard UL 94V-0)
- Supplied with 480 cm connection cable and canopy

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

EDL-412/WS

Active/passive

passive

EDL-412/WS

Transmission technology	100 V or low-impedance
Total power rating	10 W
Power rating (RMS)	10/5/2.5 W
Impedance	8 Ω
Frequency range	160-20,000 Hz
Full range speaker	130 mm (5")
Number of speakers	1
Speaker size	13 cm (5")
SPL	92 dB/W/m
Radiation angle/beam angle	100°
Radiation angle, horizontal	100°
Radiation angle, vertical	100°
Housing material	ABS, UL 94V-0
Colour	white
Mounting device	cable with canopy
Protection class	IP44
Admiss. ambient temp.	-30 °C to +40 °C
Dimensions	Ø 184 mm
Width	Ø 184 mm
Height	Ø 184 mm
Depth	Ø 184 mm
Weight	1.65 kg
Inputs	cable connection
Packaging dimensions (W x H x L)	0.3 x 0.22 x 0.23 m
Gross weight	2 kg
Net weight	1.65 kg

EDL-412/WS

EAN code	4007754189124
Net weight	1.65 kg