



NAC3FPX-TOPSB

Order No.: 0034164

PRODUCTINFOS

NEUTRIK POWERCON True1 TOP Connectors

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ~ 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Robust version with latching device and cable inlet with self-adjusting clamps (plug and inline jack only)
- Self-extinguishing according to UL 94V-0
- Protection class IP65 (NAC3FX-W-TOP and NAC3MX-W-TOP)

NEUTRIK POWERCON True1 TOP panel jack

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ~ 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Self-extinguishing according to UL 94V-0

Manufacturer information:

Neutrik AG
Im alten Ried 143
9494 Schaan
Liechtenstein
neutrik@neutrikgroup.com

TECHNICAL SPECIFICATIONS

NAC3FPX-TOPSB

Description	panel jack
Type	NEUTRIK POWERCON TOP
Quantity	1
Features	latching device
Colour/colour coding	black
Power rating	~ 250 V/16 A
Insulating resistance	> 100 MΩ
Dielectric strength	DC 4 kV/~ 2.8 kV
Certification	UL, VDE
Pole number	2+PE
Connection	blade terminals, 6.35 mm
Material	plastic
No. of contacts	2
Admiss. ambient temp.	-30-+80 °C
Dimensions	35.4 x 35.4 x 43 mm
Length	43 mm
Weight	20 g

NAC3FPX-TOPSB

EAN code	7613187011801
Net weight	0.02 kg