



# DRM-882LAN

Order No.: 0179250

## PRODUCTINFOS

### Digital 8x8 matrix router

- 8 inputs and 8 outputs (plug-in screw terminals, switchable mic/line, balanced)
- +48 V phantom power
- User-defined routing of the inputs to the outputs
- The level of each routed input can be adjusted per assigned output (individual output mix)
- Up to 32 devices can be managed via software
- A/D converter: 4 x 24 bits, D/A converter: 1 x 24 bits
- Extensive signal processing and monitoring, e.g. frequency shift feedback eliminator, parametric 5-band equalizer with peak and shelving filters, variable low-pass/high-pass filters - optionally with Bessel, Butterworth or Linkwitz-Riley characteristics, RMS compressor, peak limiter, selectable phase, delay
- Integrated auto mixer
- 6-fold LED status cluster for each channel
- 6 user presets can be accessed directly
- Link feature for simultaneously changing the settings of several channels
- Stereo mode for the channels 1/2, 3/4, 5/6 and 7/8
- Dot matrix display with 2 x 24 characters
- Remote control via USB, RS-485 or TCP/IP LAN
- Real-time remote control via software
- Lock mode for front panel control
- Individual room control via optional wall-mounted remote control panel DRM-882WP or DRM-882WPX
- Robust steel housing with aluminium front panel
- 482 mm (19") rack installation, 1 RU

### Input (data for each channel):

- Gain control with 0 dB bypass function
- Noise gate
- Mic/line switching

- Selectable priority circuit
- Parametric 3-band equalizer (peak, low-pass shelving, high-pass shelving)
- Frequency shift feedback eliminator
- Selectable phase (180°)

**Output (data per channel):**

- Low-pass filter/high-pass filter with Butterworth, Linkwitz-Riley and Bessel characteristics (to -24 dB/oct.). Even higher slopes possible in combination with equalizer
- Parametric 5-band equalizer with peak or low-pass/high-pass shelving filters
- Peak limiter and RMS compressor with a ratio of up to 32:1 and continuously adjustable soft/hard knee characteristics. Threshold: 18 dBu to -12 dBu, release time: 0.1-3 s, attack time: 5-200 ms
- Peak limiter and RMS compressor with bypass function
- Switchable delay between time (ms) and distance (m): 380.998 ms max. in steps of 21 µsec or 129.539 m max. in steps of 6.8 mm
- Selectable phase (180°)
- Gain control

**Manufacturer information:**

MONACOR INTERNATIONAL GmbH & Co. KG  
Konsul-Smidt-Str. 68  
28217 Bremen  
Germany  
info@monacor.com

**Safety Notes and Warning Messages**

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

**TECHNICAL SPECIFICATIONS****DRM-882LAN**

Description

matrix router

**DRM-882LAN**

|                       |                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------|
| Frequency range       | 20-20,000 Hz                                                                              |
| Input signal          | 6.2 V max.                                                                                |
| Output signal         | 6.2 V max.                                                                                |
| Crossover frequency   | 70 Hz-1 kHz, 12 dB/oct.,<br>910 Hz-8 kHz, 12 dB/oct.,<br>subwoofer: 80/120 Hz, 24 dB/oct. |
| S/N ratio             | > 104 dB                                                                                  |
| THD                   | < 0.005%                                                                                  |
| Admiss. ambient temp. | 0-40 °C                                                                                   |
| Power supply          | ~ 230 V/50 Hz/20 VA                                                                       |
| Dimensions            | 482 x 44 x 250 mm, 1 RU                                                                   |
| Weight                | 3.4 kg                                                                                    |
| Inputs                | 8 x plug-in screw terminal, bal.                                                          |
| Outputs               | line: 8 x plug-in screw terminal, bal.                                                    |
| Other features        | USB, RS-485, TCP/IP                                                                       |

**DRM-882LAN**

|            |               |
|------------|---------------|
| EAN code   | 4007754272468 |
| Net weight | 3.47 kg       |