



WDR-130-CX10



Order No.: 1001494

PRODUCTINFOS

PA ceiling speaker

- 100 V transmission technology
- 2-way speaker system (13 cm)
- High sound quality and well-balanced frequency response, distortion-free transmission of 50 Hz signals also possible
- Quick-mounting device
- Metal housing with metal protective grille
- 3 power taps via pressure clamps
- Ball-proof in accordance with DIN 18 032, part 3

Manufacturer information:

PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

TECHNICAL SPECIFICATIONS

WDR-130-CX10

Transmission technology	100 V
Frequency range	50-22,000 Hz
Power rating (RMS)	10/5/2.5 W
SPL	91 dB/W/m
Max. rated SPL	101 dB
Radiation angle, horizontal	180°
Radiation angle, vertical	180°
Mounting cutout	Ø 140-150 mm
Dimensions	Ø 167 mm x 98 mm
Outside diameter	Ø 167 mm
Width	Ø 167 mm
Height	Ø 167 mm
Depth	98 mm
Colour	white, RAL 9010
Weight	1.4 kg
Packing unit	1
Type of speaker	130
Packaging dimensions (W x H x L)	0.187 x 0.187 x 0.1 m
Gross weight	1.5 kg
Net weight	1.4 kg

WDR-130-CX10

EAN code	4007754430271
Net weight	1.4 kg