



ECM-306B/WS

Order No.: 0235800

PRODUCTINFOS

Boundary microphone

- On/off switch with power LED
- Low cut and 10 dB attenuation, switchable
- Integrated electronics for the direct connection to a phantom power supply DC 17-48 V
- Electronically balanced AF output
- 6 m connection cable with 3-pole mini XLR/XLR plug
- Supplied in a foam-padded plastic case

Especially suitable for the use as a desktop microphone!

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

ECM-306B/WS

Description	boundary microphone
Transmission method	cable
Polar pattern	semi-supercardioid
System	electret
Audio frequency range	30-20,000 Hz
Nominal impedance	250 Ω
Sensitivity	22 mV/Pa
Max. sound pressure	130 dB
Power supply	DC 17-48 V, phantom power
Admiss. ambient temp.	0-40 °C
Dimensions	90 x 25 x 90 mm
Weight	200 g
Cable	6 m
Connection	3-pole mini XLR/XLR
Packaging dimensions (W x H x L)	0.145 x 0.06 x 0.215 m
Gross weight	0.495 kg
Net weight	0.322 kg

ECM-306B/WS

EAN code	4007754212761
Net weight	0.322 kg