




PRIMA-VA/680RC

Order No.: 1001529

PRODUCTINFOS

Manufacturer information

ATEIS Deutschland GmbH
Bahnhofstr. 18
74906 Bad Rappenau
Germany
info.de@ateis.global
www.ateis-deutschland.de

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

During operation, there may be a hazard of contact with a dangerous voltage of up to 100 V at the speaker terminals. Always switch off the amplifier before making or changing any connections.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated inside the unit must be dissipated by air circulation; never cover the air vents of the housing.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

PRIMA-VA/680RC

Peak output power	800 W
Power rating	800 W
Power rating at 100 V	
Zones	6
Inputs	
Frequency range	20-20,000 Hz
S/N ratio	87 dB
THD	< 0.2%
Phantom power	DC 24 V
Power supply	
Mains voltage	~ 230 V
Mains frequency	
Admiss. ambient temp.	-10 °C to +50 °C
Width	482 mm
Height	88 mm
Depth	432 mm
Rack units, RU	
Weight	8.2 kg
Connections	
Packaging dimensions (W x H x L)	
Gross weight	9.9 kg
Net weight	8.2 kg

PRIMA-VA/680RC

Net weight	8.2 kg
------------	--------