



GB20T/EN

Order No.: 1001526

PRODUCTINFOS

This modern ball speaker is particularly suited for use in rooms with high ceilings.

Thanks to the wide opening angle, it provides even coverage of the listening area. The excellent sound distribution in combination with a balanced frequency response can solve many acoustic problems that arise in high rooms with difficult acoustic conditions.

The ideal area of application for these speakers is in large-volume rooms with high ceilings, such as supermarkets, department stores, airport waiting rooms and lounges, factories, etc. The GB20T is characterised by its very good speech intelligibility and reproduction of background music.

PA ball speaker

with EN 54-24 certification, 2008 0905-CPR-0284 Type B

- 100 V transmission technology
- Excellent reproduction of speech and music
- Wide sound coverage
- Elegant and simple design
- UV-resistant, reinforced ABS plastic
- Radiation angle horizontal 360° and vertical 140-160°
- 4.7 m connection cable with canopy included

Manufacturer information

ATEIS Deutschland GmbH
Bahnhofstr. 18
74906 Bad Rappenau
Germany
info.de@ateis.global
www.ateis-deutschland.de

TECHNICAL SPECIFICATIONS

GB20T/EN

Active/passive	passive
Transmission technology	cable
Total power rating	20 W
Power rating (RMS)	
Frequency range	80-18,000 Hz
System	
Number of speakers	1
Speaker size	
SPL	
Max. rated SPL	
Radiation angle/beam angle	
Radiation angle, horizontal	
Radiation angle, vertical	
Housing material	
Colour	
Mounting device	
Protection class	
Admiss. ambient temp.	-25 °C to +70 °C
Dimensions	
Width	Ø 154 mm
Height	154 mm
Depth	Ø 154 mm
Weight	2.42 kg
Inputs	
Packaging dimensions (W x H x L)	
Net weight	2.42 kg

GB20T/EN

EAN code

3760439320960

Net weight

2.42 kg