



TXA-822CD

Order No.: 0179070

PRODUCTINFOS

Portable amplifier system,

with integrated 2-channel multifrequency receiver unit with UHF PLL technology and Bluetooth receiver.

- Operation via mains connection or built-in rechargeable lead gel battery 2 x 12 V/4.5 Ah (operating time: up to 5 hours), integrated automatic battery charging with charging status indication, deep discharge protection
- For mobile applications, e.g. sales events, lectures
- 2 x 16 selectable UHF frequencies (863-865 MHz)
- CD player with anti-shock system, MP3 reproduction and slot-in mechanism
- SD card reader, USB port
- Pitch control function
- Supplied with remote control for CD player
- 1 radio transmitter for wireless audio link operation of several TXA-820 systems
- Efficient 2-way speaker system
- 1 microphone input via comb. jack (XLR/6.3 mm), 1 microphone input (6.3 mm jack), 1 stereo line input (RCA), 1 aux input (3.5 mm jack), each input can be adjusted
- Common master control, 2-way tone control
- 1 stereo line output (RCA), 1 aux output (3.5 mm jack)
- Switchable microphone priority circuit
- Due to an extractable telescopic handle and 2 castors, the amplifier system can easily be pulled like a

trolley

- Stand sleeve

Licence-free within the EU.

Matching microphone transmitters or pocket transmitters are available at option, e.g. TXA-800HSE, TXA-800HT or ATS-12HT.

Audio link operation:

The integrated radio transmitter of the TXA-822CD and TXA-1022CD transmits audio signals to one or several TXA-820 or TXA-1020 systems. Ideally suited for larger indoor PA applications where a consistent sound radiation is required.

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Warning and Safety Instructions

The device is supplied with dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Risk of electric shock!

Do not use this device and disconnect it immediately from the power supply if the device or the power supply cable is visibly damaged, if a defect might have occurred after the device was dropped or suffered a similar accident, if malfunctions occur. Any repairs must be carried out by specialists.

The product is suitable for indoor use only. Protect it against dripping water, splash water and high air humidity (admissible ambient temperature range is 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated in the device must be dissipated by air circulation. Never cover the air vents of the housing.

If the device is to be put out of operation definitely, dispose of the product in accordance with local regulations.

Never put (rechargeable) batteries in the household waste. Always dispose of the batteries in accordance with local regulations.

- Portable amplifier system with multi-frequency receiver and Bluetooth

TECHNICAL SPECIFICATIONS

TXA-822CD

Rated power (P_{RMS})	50 W
Peak output power	80 W
Frequency range	70-17,000 Hz
Carrier frequency	863-865 MHz
Operating range	≈ 30 m
Inputs	6 mV (mic), 300 mV (line)
Link	wireless
Max. SPL	114 dB
Equalizer, bass	± 10 dB/100 Hz
Equalizer, treble	± 10 dB/10 kHz
Power supply	~ 230 V/50 Hz/130 VA, rech. battery 2 x 12 V/4.5 Ah
Admiss. ambient temp.	0-40 °C
Dimensions	305 x 510 x 265 mm
Weight	15.5 kg
Connections	1 x XLR/6.3 mm jack (mic/line), 1 x 6.3 mm jack (mic) 1 x RCA L/R (line out), 1 x 3.5 mm jack (line out)

TXA-822CD

EAN code	4007754269574
Net weight	15.7 kg