



HSE-150/SK

Order No.: 0234050

PRODUCTINFOS

Ultra-light headband microphone

Suitable for the reproduction of vocals and speech for any kind of audio transmission. A high-quality back electret cartridge with omnidirectional polar pattern provides a good sound of a high quality even if the cartridge is not perfectly aligned. An ergonomic design is the reason for both an unobtrusive and secure fit even during extreme head movements.

- Wide transmission range
- Very comfortable to wear
- Stable positioning
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all TXS-...HSE pocket transmitters with 3-pole mini XLR connection
- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Ultra-light headband microphone

- Omnidirectional polar pattern

- High-quality back electret cartridge
- 3-pole mini XLR connection
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Compatible with all TXS-...HSE pocket transmitters with 3-pole mini XLR connection
- External power supply, e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

tools4music 03/2012

“During the test with well-known reference units, it emerged that a real price-performance tip is now available from the audio distributor in Bremen, Germany: the HSE-150/SK. Conclusion: anyone who wants to invest in new headsets with a good price-performance ratio for every-day use should try out the HSE-150/SK and the earband microphone HSE-70A/SK in a personal test environment.”

+ Comfortable to wear

+ Well-balanced sound tuning

+ Very good price-performance ratio

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

HSE-150/SK

Description	headband microphone
Transmission method	cable
Polar pattern	omnidir.
System	back electret
Audio frequency range	20-20,000 Hz
Nominal impedance	1 kΩ
Sensitivity	8 mV/Pa
Max. sound pressure	130 dB
Power supply	DC 1.5-9 V
Admiss. ambient temp.	0-40 °C
Weight	7 g
Connection	3-pole mini XLR

HSE-150/SK

Packaging dimensions (W x H x L) 0.15 x 0.06 x 0.2 m

Gross weight 0.116 kg

Net weight 0.015 kg

HSE-150/SK

EAN code 4007754183719

Net weight 0.015 kg