




NTE-10/3

Order No.: 0212380

PRODUCTINFOS

Audio transformer 1:3/1:10 for microphone signals,

from NEUTRIK.

- Very compact design, e.g. also suitable for installation into connector housings
- Unshielded version with bare wire connections (70 mm)
- Wideband version
- Balance adjustment
- Galvanic isolation to avoid/eliminate hum loops
- Max. input voltage: 350 mV/380 mV (1% THD/50 Hz)

When installing unshielded transformers into units with interference fields (e.g. power transformers), attention has to be paid to respective shielding measures.

Manufacturer information:

Neutrik AG
Im alten Ried 143
9494 Schaan

Liechtenstein
neutrik@neutrikgroup.com

TECHNICAL SPECIFICATIONS

NTE-10/3

Description	transformer
Frequency range	20-20,000 Hz
Input signal	380 mV
Input impedance	200 Ω
Output impedance	10 k Ω /50 k Ω
Transmission ratio	1:3/1:10
Admiss. ambient temp.	0-40 °C
Dimensions	14 x 11 x 12 mm (w/o cable)
Weight	7 g
Inputs	bare wire connections
Outputs	bare wire connections

NTE-10/3

EAN code	4007754208771
Net weight	7.3 g

NTE-10/3

Width	14 mm
Height	11 mm
Depth	12 mm
Weight	7.3 g