



DRM-884RC

Order No.: 0176990

PRODUCTINFOS

PA zone paging microphone,

for audio matrix router DRM-884.

- LCD for selected zones (1-32), volume and ID number
- LED indication for signal status
- Volume control (assignable for each zone)
- Zone selector control
- Momentary push-to-talk button
- Plug-in electret gooseneck microphone (NEUTRIK 3-pole XLR jack)
- USB port for loading sound files containing chimes
- Power supply via audio matrix router DRM-884
- Connection to DRM-884 via RJ45 jack and Cat. 5e network cable (supplied w/o cable), cable length up to 100 m

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen

Germany
info@monacor.com

Safety and warning notices

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).

Do not operate the appliance if there is visible damage to the appliance, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialised workshop for repair.

If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

TECHNICAL SPECIFICATIONS

DRM-884RC

Description	PA zone paging microphone
Transmission method	cable
Gooseneck length	310 mm
Admiss. ambient temp.	0-40 °C
Dimensions	176 x 70 x 162 mm
Weight	811 g
Connection	RJ45, micro USB
Packaging dimensions (W x H x L)	0.255 x 0.105 x 0.395 m
Gross weight	1.197 kg
Net weight	0.811 kg

DRM-884RC

EAN code	4007754261820
Net weight	0.811 kg