



ESP-250/WS

Order No.: 0162780

PRODUCTINFOS

PA speaker system,

in a weatherproof white plastic cabinet with aluminium protective grille.

- 100 V transmission technology
- Hose-proof
- Switchable to 8 Ω operation
- 5 power taps, 8 Ω connection and 100 V power selector switch
- 2-way system
- Stainless steel mounting bracket

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

ESP-250/WS

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	100 W
	50/40/30/20/10 W (100 V)
Power rating (RMS)	50 W (8 Ω)
Impedance	8 Ω
Frequency range	80-20,000 Hz
System	2-way
Number of speakers	2
Speaker size	13 cm (5")
SPL	92 dB/W/m
Radiation angle/beam angle	H: 120°/V: 100°
Radiation angle, horizontal	120°
Radiation angle, vertical	100°
Housing material	plastic
Colour	white
Mounting device	mounting bracket
Protection class	IP65
Admiss. ambient temp.	-30 °C to +50 °C
Dimensions	157 x 260 x 170 mm
Width	157 mm
Height	260 mm
Depth	170 mm
Weight	2.4 kg
Inputs	spring-load. speaker term.
Packaging dimensions (W x H x L)	0.2 x 0.2 x 0.29 m
Gross weight	2.68 kg
Net weight	2.38 kg

ESP-250/WS

EAN code	4007754218411
Net weight	2.38 kg