

92x92x38mm (3.62x3.62x1.50in) - 7 blade



Bearing System— 2 Ball Bearing
 Life Expectancy— Ball 70000hrs@ 25°C
 Frame----- Thermoplastic PBT+30% GF, UL94-V0
 Impeller----- Thermoplastic PBT+15% GF, UL94-V0
 Lead Wire----- UL 1007, AWG 24, 260±10mm, Red(+), Black(-)
 Protection----- Locked rotor protection
 IP Grade ----- Optional



Dim: 553x339x245 mm
 N.W.: 13.5 kgs
 G.W.: 15.0 kgs
 Q'TY: 60 pcs

FUNCTIONS	PART NUMBER	RATED (VDC)	LABEL CURRENT	ACTUAL CURRENT	POWER (WATTS)	SPEED (RPM)	AIRFLOW (CFM)(m³/min)	PRESSURE (mmAq)(In H²O)	NOISE (dBA)	WEIGHT (Q'TY/CTN)		
1b:AS 2a:FG 2b:RD 2c:RD 6:CL	R9238H12BPLBxy-7	12 (07~14)	1.850	1.560	18.72	6500	132.94	3.76	22.88	0.90	59.10	225g (60pcs)
	R9238M12BPLBxy-7		0.820	0.640	7.68	5000	102.26	2.90	13.54	0.53	52.20	
	R9238L12BPLBxy-7		0.330	0.292	3.50	3500	71.58	2.03	6.63	0.26	43.00	
	R9238H24BPLBxy-7	24 (15~27)	0.810	0.720	17.28	6500	132.94	3.76	22.88	0.90	59.10	225g (60pcs)
	R9238M24BPLBxy-7		0.430	0.340	8.16	5000	102.26	2.90	13.54	0.53	52.20	
	R9238L24BPLBxy-7		0.170	0.152	3.65	3500	71.58	2.03	6.63	0.26	43.00	
	R9238H48BPLBxy-7	48 (36~57)	0.390	0.351	16.85	6500	132.94	3.76	22.88	0.90	59.10	225g (60pcs)
	R9238M48BPLBxy-7		0.200	0.176	8.45	5000	102.26	2.90	13.54	0.53	52.20	
	R9238L48BPLBxy-7		0.100	0.080	3.84	3500	71.58	2.03	6.63	0.26	43.00	

Remark:

1. Part no. suffix: "xy"=Function detail or "x"=Function number, "y"=customer ID

2. R series - STANDARD series:

Uses a 2 coil complementary type drive offering low cost, applicable for higher power demanding applications and have more functions,

