

MNX PC 300/150 ZT



Sample photo

Order symbol: PC 300/150 ZT
Product nbr: 6017938
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074061522
El. number:
Finland: 3435626
Electric No. Denmark: 8212027996
Electric No. Sweden: 6017938

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:			Accessories:	
Length	Width	Height	MIV 200	Mounting plate (Galvanized steel)
mm:	360	255	MIV 150	Mounting plate (Galvanized steel)
inch:	14.2	10.0	MIN 20	DIN-15 Mounting rail
Materials:			MIN 15	DIN-15 Mounting rail
Material:	Polycarbonate		MIV 30	DIN-35 Mounting rail
Base colour:	RAL 7035 -light grey		MIV 20	DIN-35 Mounting rail
Cover screws material:	Polyamide		MIV 15	DIN-35 Mounting rail
Cover colour:	Smoked grey		FP 10674	
Cover screws colour:	Black		Rating:	
Gasket material:	Polyurethane		Ingress Protection (EN 60529): IP66/IP67	
Temperatures:			Impact Resistance (EN 62262): IK08	
Temperature °C (short term):	-40 ... 120 °C		Electrical insulation: Totally insulated	
Temperature °C (continuous):	-40 ... 80 °C		Halogen free (DIN/VDE 0472, Part 815): 1	
Temperature °F (short term):	-40 ... 250 °F		UV resistance: UL 508	
Temperature °F (continuous):	-40 ... 175 °F		Flammability Rating: UL 746C 5"	
Accessories:			Glow Wire Test (IEC 695-2-1) °C: 960	
MIV 300	Mounting plate (Galvanized steel)		NEMA Class: NEMA 1, 4, 4X and 6	

