



ESP-62/WS

Order No.: 0163030

PRODUCTINFOS

PA wall speaker,

with EN 54-24 certification.

- 100 V transmission technology via audio transformer with 3 power taps
- Full range speaker with a high-quality sound and a clear voice reproduction
- Plastic cabinet of a special design (open rear panel) with protective metal grille
- Symmetrical design allows for horizontal and vertical mounting
- Supplied with mounting screws and screw head covers
- Ball-proof according to DIN 18032, Part 3

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

ESP-62/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	6 W
Power rating (RMS)	6/3/1.5 W
Frequency range	100-19,000 Hz
Number of speakers	1
Speaker size	13 cm (5")
SPL	93 dB (1 W/1 m)
	76 dB (EN, 1 W/4 m)
Max. rated SPL	101 dB (1 m)
	86 dB (EN, 4 m)
Radiation angle/beam angle	H180°/V180° (500 Hz)
	H180°/V180° (1 kHz)
	H180°/V1115° (2 kHz)
	H51°/V68° (4 kHz)
	180° (500 Hz)
Radiation angle, horizontal	180° (1 kHz)
	180° (2 kHz)
	51° (4 kHz)
Radiation angle, vertical	180° (500 Hz)
	180° (1 kHz)
	115° (2 kHz)
	68° (4 kHz)
Housing material	plastic
Colour	white, RAL9010
Mounting device	mounting screws
Protected against ball rebound	yes
Admiss. ambient temp.	-10 °C to +50 °C
Dimensions	240 x 330 x 85 mm
Width	240 mm
Height	330 mm
Depth	85 mm
Weight	1.2 kg
Inputs	screw terminals
Packaging dimensions (W x H x L)	0.245 x 0.1 x 0.345 m
Gross weight	1.532 kg
Net weight	1.242 kg

ESP-62/WS

EAN code 4007754227475

Net weight 1.242 kg