



TXA-802SR

Order No.: 0172990

PRODUCTINFOS

Professional 16-channel Mono PLL Audio Transmission System, 863-865 MHz, with Extensive Accessories

- Compatible with portable amplifier systems TXA-624CD/SW, TXA-604/SW and the TXA-820 and TXA-1020 series
- In addition to the combination with TXA-624CD/SW, TXA-604/SW and the TXA-820 and TXA-1020 series, it can also be used as a tour guide system and for any other application in which a certain audio source or voice source is to be distributed to one or more receivers
- Can be combined with transmitters and receivers of the ATS-16 series
- Simultaneous operation of up to 4 transmitters with different frequencies (dep. on distance of transmitters, stationary RF sources of interference and other local conditions)
- Licence-free in the EU

2-channel multifrequency receiver,

with UHF PLL technology.

- Matching the transmitters TXA-800HT, TXA-800HSE, TXA-800ST and ATS-12HT
- 2 x 16 selectable UHF frequencies (863.1-864.9 MHz) with diversity system

- Scan function for free channel
- Volume control
- LCD for indicating selected channel and carrier signal
- Balanced XLR output and 6.3 mm jack output
- 482 mm (19") rack installation of 2 devices is possible with supplied mounting brackets
- Power is provided via enclosed plug-in power supply
- Dimensions: 215 x 50 x 210 mm
- Weight: 1.2 kg

Licence-free in the EU.

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

TXA-802SR

General information

Description	receiver unit
Carrier frequency range	863.1-864.9 MHz
Channels	2
Admiss. ambient temp.	0-40 °C

Specifications receiver

TXA-802SR

Audio signal receiver	30 mV (XLR), 730 mV (6.3 mm jack, high), 80 mV (6.3 mm jack, low)
Power supply receiver	via encl. plug-in power supply
Width receiver	215 mm
Height receiver	50 mm
Depth receiver	210 mm
Weight receiver	1.2 kg
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.

TXA-802SR

EAN code	4007754249279
Net weight	1.34 kg