



## EDL-530EN/SW

Order No.: 1000261

### PRODUCTINFOS

#### High-quality PA pendant speaker,

with EN 54-24 certification.

- 100 V transmission technology or 8  $\Omega$  operation
- 2-way coaxial system (5.25")
- UV-resistant ABS housing with aluminium grille
- Excellent sound quality for speech and music
- 5 m safety rope
- Plug-in screw terminal

#### Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG  
Konsul-Smidt-Str. 68  
28217 Bremen  
Germany  
[info@monacor.com](mailto:info@monacor.com)

## TECHNICAL SPECIFICATIONS

### EDL-530EN/SW

|                                  |                                               |
|----------------------------------|-----------------------------------------------|
| Active/passive                   | passive                                       |
| Transmission technology          | 100 V or low-impedance                        |
| Total power rating               | 30 W                                          |
| Power rating (RMS)               | 30/15/7.5/3.8 W                               |
| Impedance                        | 8 $\Omega$                                    |
| Frequency range                  | 65-20,000 Hz                                  |
| System                           | 2-way coaxial                                 |
| Bass speaker                     | 13.33 cm (5.25")                              |
| Tweeter                          | 25 mm (1")                                    |
| Number of speakers               | 2                                             |
| Speaker size                     | 13.33 cm (5.25")                              |
| SPL                              | 90 dB/W/m                                     |
| Radiation angle/beam angle       | 120°                                          |
| Radiation angle, horizontal      | 120°                                          |
| Radiation angle, vertical        | 120°                                          |
| Housing material                 | ABS                                           |
| Colour                           | black                                         |
| Mounting device                  | Eyelet bolt and 5 m steel rope with snap hook |
| Admiss. ambient temp.            | 0-40 °C                                       |
| Dimensions                       | Ø 195 mm x 250 mm                             |
| Width                            | Ø 195 mm                                      |
| Height                           | 250 mm                                        |
| Depth                            | Ø 195 mm                                      |
| Weight                           | 2.26 kg                                       |
| Inputs                           | plug-in screw terminal                        |
| Packaging dimensions (W x H x L) | 0.22 x 0.3 x 0.22 m                           |
| Gross weight                     | 2.66 kg                                       |
| Net weight                       | 2.26 kg                                       |

### EDL-530EN/SW

|            |               |
|------------|---------------|
| EAN code   | 4007754276961 |
| Net weight | 2.26 kg       |