



WDR-130-F-EN-10



Order No.: 1001418

PRODUCTINFOS

PA ceiling loudspeaker

with EN 54-24 certification.

- 100-volt transmission technology
- Speaker (13 cm) with high sound pressure and very good transmission range
- Moisture-protected speaker cone
- Fire pot
- Quick mounting device
- Metal housing with metal protective grille
- 3 power taps via WAGO terminal
- Ball impact resistance test according to DIN 18 032, part 3

Manufacturer information:

PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

TECHNICAL SPECIFICATIONS

WDR-130-F-EN-10

Transmission technology	100 V
Frequency range	80-19,000 Hz
Power rating (RMS)	10/5/2.5 W
SPL	93 dB (1 W/1 m) 78 dB (EN, 1 W/4 m)
Max. rated SPL	103 dB (1 m) 88 dB (EN, 4 m)
Radiation angle, horizontal	180° (500 Hz) 180° (1 kHz) 155° (2 kHz) 76° (4 kHz)
Radiation angle, vertical	180° (500 Hz) 180° (1 kHz) 155° (2 kHz) 76° (4 kHz)
Mounting cutout	Ø 140-150 mm
Dimensions	Ø 167 mm x 90 mm
Outside diameter	Ø 167 mm
Width	Ø 167 mm
Height	Ø 167 mm
Depth	90 mm
Colour	white, RAL 9010
Protective class	IP54
Weight	1.1 kg
Packing unit	1
Type of speaker	130
Packaging dimensions (W x H x L)	0.187 x 0.187 x 0.090 m
Gross weight	1.2 kg
Net weight	1.1 kg

WDR-130-F-EN-10

EAN code	4007754429534
Net weight	1.1 kg