



Europa Series Terminal Blocks

230 - Conductor size 4 mm²

Approvals Click for Approvals (PDF)					
Nominal cross-section mm²	2,5	2,5	22-12 AWG 30 amp.	24-12 AWG 25 amp.	
Voltage rating V	450	450	150/250	300	

Technical data

Connection	screw conductor size 0.5 - 4.0 mm ²
Fixing	by screw or rivet size Ø 2.8 mm
Mouldings	polyamide 6, natural flammability rating to UL 94: V-2 continuous working temperature 100 °C short-time temperature 160 °C
Contacts	brass, plated
Screws	M3; ⚙ Tightening torque 0.5 Nm steel, zinc plated, chromed
Current rating	to EN 60598: 16 A: 16 A at T 85 °C to EN 60998: 24 A: 24 A at T 85 °C
Stripping length	5 - 5.5 mm



Order info

Description	Item	Order No.	PU
1 pole	230/ 1	121201	1000
2 pole	230/ 2	121202	3000
3 pole	230/ 3	121203	2000
4 pole	230/ 4	121204	500
5 pole	230/ 5	121205	500
6 pole	230/ 6	121206	500
12 pole	230/12	121212	50

Variants

230 K Conductor size 4 mm², raised base

Accessories

230 BZ	Marking labels for types 230 (printed or unprinted)
ZEL 110	universal, screwless strain relief clamp

Upon request

7 - 11 pole, printing, different polyamides (in particular glow wire to EN 60335-1 and PA 6.6 HT for high temperatures), different screws