



WDC-903M



Order No.: 1001180

PRODUCTINFOS

Digital wireless conference system,

with Dante® connection.

- For local government departments, business meeting rooms, business premises and international conference centres
- Professional design, perfect circuit setup and reliable functional characteristics
- Can be combined with compatible automatic motion tracking system
- LoRa protocol with low latency for two-way communication
- With interference protection, which sufficiently suppresses interferences caused by computers, mobile phones and wireless Bluetooth devices nearby
- Carrier frequency: 522-554 MHz
- Sampling rate: 48 kHz/24 bits
- Operating range: up to 80 m
- 482 mm (19") rack installation, 1 RU

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Please note: RELACART products are distributed by MONACOR INTERNATIONAL exclusively in the following countries: Germany, Austria, Switzerland, Netherlands, Belgium, Luxembourg, Denmark, Portugal, Malta. Orders from other countries cannot be fulfilled.

Manufacturer information:

Relacart Electronics Co., Ltd.
1408 Room, B Building
Fengxing Plaza
No. 242, Tianhe Road
Tianhe District
Guangzhou, Guangdong
China
info@relacart.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

TECHNICAL SPECIFICATIONS

WDC-903M**General information**

Description	receiver unit
Carrier frequency range	522-554 MHz
Audio frequency range	50-18,000 Hz
Channels	6
THD	< 0.5%
RF S/N ratio	> 100 dB

Specifications receiver

Power supply receiver	~ 110-240 V/50-60 Hz
Width receiver	480 mm
Height receiver	43 mm
Depth receiver	350 mm
Weight receiver	3.2 kg
Connections receiver	1 x XLR, bal. (out), 1 x RCA L/R (aux out), 2 x RJ45 (Dante®)

WDC-903M

EAN code	4007754426601
Net weight	3.94 kg