



EUL-26/SW

Order No.: 0163280

PRODUCTINFOS

Pairs of miniature PA speaker systems

- Speakers for general applications, very small dimensions, 100 V transmission technology
- Can also be connected at 8 Ω
- 6.5 cm (2.5") full range speaker
- Good sound characteristics and speech intelligibility
- Turnable, wall bracket with ball joint allows for pivoting and tilting
- An additional subwoofer system is recommended for complementing the low-frequency music reproduction (e.g. EUL-2SUB/SW, SOUND-100SUB)

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

EUL-26/SW

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	20 W
Power rating (RMS)	6 W (100 V) 10 W (8 Ω)
Impedance	8 Ω
Frequency range	150-20,000 Hz
Number of speakers	1
Speaker size	6.5 cm (2.5")
SPL	88 dB/W/m
Radiation angle/beam angle	150°
Radiation angle, horizontal	150°
Radiation angle, vertical	150°
Housing material	plastic
Colour	black
Mounting device	wall bracket
Admiss. ambient temp.	0-40 °C
Dimensions	90 x 90 x 115 mm
Width	90 mm
Height	90 mm
Depth	115 mm
Weight	0.65 kg
Inputs	spring-load. speaker term.
Other features	pair
Packaging dimensions (W x H x L)	0.11 x 0.11 x 0.295 m
Gross weight	1.446 kg
Net weight	1.318 kg

EUL-26/SW

EAN code	4007754241945
Net weight	1.318 kg