




8Ω

SPE-15/WS

Order No.: 0105600

PRODUCTINFOS

Hi-fi wall and ceiling speaker, 8 Ω

- 2-way version with dome tweeter
- Plastic housing with protective metal grille
- ABS plastic material, self-extinguishing according to UL 94V-0
- Excellent sound characteristics
- For a wall thickness/ceiling thickness from 8 to 35 mm

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

SPE-15/WS

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	60-20,000 Hz
Resonant frequency (fs)	90 Hz
Power rating (RMS)	25 W
Peak music power output (MAX)	50 W
SPL	87 dB/W/m
Mounting cutout	115 x 190 mm
Mounting depth	61 mm
Dimensions	146 x 220 x 70 mm
Width	146 mm
Height	220 mm
Depth	70 mm
Colour	white
Admiss. ambient temp.	0-40 °C
Weight	0.83 kg
Packing unit	1
Type of speaker	100
Packaging dimensions (W x H x L)	0.195 x 0.095 x 0.265 m
Gross weight	0.989 kg
Net weight	0.879 kg

SPE-15/WS

EAN code	4007754232677
Net weight	0.879 kg