



ZM-100

Order No.: 0171950

PRODUCTINFOS

Impedance meter,

for measuring the impedance (Z) of individual speakers or speaker lines.

- Measurement with pulsed 1 kHz signal
- Processor-controlled with independent selection of the most favourable measuring range
- Power received at the mains of the 100 V speaker is calculated and displayed
- Range button and hold button
- Measuring ranges: 200 Ω /2 k Ω /20 k Ω /200 k Ω
- Power supply via 4 x 1.5 V battery AA size
- Dimensions: 100 x 177 x 50 mm
- Weight: 570 g
- Supplied with protective bag and pair of test leads

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany

info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

Safety Notes and Warning Messages

During operation, there may be a hazard of contact with a dangerous voltage at the speaker terminals of an amplifier.

Only perform measurements on speakers or speaker lines which are disconnected from the amplifier. If an amplifier is connected, this will result in measurement errors and may damage the meter. Switch off the amplifier before disconnecting the speakers from the amplifier.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

TECHNICAL SPECIFICATIONS

ZM-100

Description	impedance meter
Nominal value	impedance (Z)
Type	measuring ranges: 200 Ω/2k Ω/20 kΩ/200 kΩ
Colour	black
Suitable for	individual speakers, speaker lines
Power supply	4 x 1.5 V batt. AA size
Admiss. ambient temp.	0-40 °C
Dimensions	100 x 177 x 50 mm
Weight	422 g
Other features	measurement with pulsed 1 kHz signal

ZM-100

Packing unit	1
Packaging dimensions (W x H x L)	0.15 x 0.085 x 0.225 m
Gross weight	0.545 kg
Net weight	0.422 kg

ZM-100

EAN code	4007754183399
Net weight	0.422 kg